APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/769,956	01/25/2001	William J. Walker	COMP:0041/FLE(P00-2992)	5915

7590	10/03/2003

Michael G. Fletcher
Fletcher, Yoder & Van Someren
P.O. Box 692289
Houston, TX 77269-2289

EXAMINER
LE, DIEU MINH T

ART UNIT	PAPER NUMBER
2184	

DATE MAILED: 10/03/2003

Please find below and/or attached an Office communication concerning this application or proceeding.

	Office Action Summary	**Application No.**	**Applicant(s)**
		09/769,956	WALKER ET AL.
		Examiner	**Art Unit**
		Dieu-Minh Le	2184

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE _3_ MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on _28 January 2002_ .

2a)☐ This action is **FINAL**. 2b)☒ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) _1-85_ is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) _1-85_ is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☒ The drawing(s) filed on _04 June 2001_ is/are: a)☒ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

11)☐ The proposed drawing correction filed on _____ is: a)☐ approved b)☐ disapproved by the Examiner.

    If approved, corrected drawings are required in reply to this Office action.

12)☐ The oath or declaration is objected to by the Examiner.

Priority under 35 U.S.C. §§ 119 and 120

13)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All b)☐ Some * c)☐ None of:

        1.☐ Certified copies of the priority documents have been received.

        2.☐ Certified copies of the priority documents have been received in Application No. _____ .

        3.☐ Copies of the certified copies of the priority documents have been received in this National Stage
application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

14)☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).

    a) ☐ The translation of the foreign language provisional application has been received.

15)☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)
2) ☒ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☒ Information Disclosure Statement(s) (PTO-1449) Paper No(s) _6_ .

4) ☐ Interview Summary (PTO-413) Paper No(s). _____ .
5) ☐ Notice of Informal Patent Application (PTO-152)
6) ☐ Other: .

Part III DETAILED ACTION

Specification

1.   Claims 1-85 are presented for examination.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35

U.S.C. 112:

> The specification shall conclude with one or more claims particularly
> pointing out and distinctly claiming the subject matter which the applicant
> regards as his invention.

2.   Claims 14-20, 83-85 are rejected under 35 U.S.C. 112,

second paragraph, as being indefinite for failing to

particularly point out and distinctly claim the subject matter

which applicant regards as the invention.

As per claim 14, line1, claim 14 can't depend on itself.

Clarification is required.

As per claims 83-85, line 1,"the method for correcting errors

detected in a memory sub-system, as set forth in claim 76" is

unclear. Claim 76 is claimed the method for dynamically

scheduling access to a memory sub-system. Correction is

required.

Claim Rejections - 35 USC § 103

3.   The following is a quotation of 35 U.S.C. 103(a) which
forms the basis for all obviousness rejections set forth in this
Office action:

(a) A patent may not be obtained though the invention is not
identically disclosed or described as set forth in section 102
of this title, if the differences between the subject matter
sought to be patented and the prior art are such that the
subject matter as a whole would have been obvious at the time
the invention was made to a person having ordinary skill in the
art to which said subject matter pertains. Patentability shall
not be negatived by the manner in which the invention was made.

4.   This application currently names joint inventors. In
considering patentability of the claims under 35 U.S.C. 103(a),
the examiner presumes that the subject matter of the various
claims was commonly owned at the time any inventions covered
therein were made absent any evidence to the contrary.
Applicant is advised of the obligation under 37 CFR 1.56 to
point out the inventor and invention dates of each claim that
was not commonly owned at the time a later invention was made in
order for the examiner to consider the applicability of 35
U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior
art under 35 U.S.C. 103(a).

5.   Claims 1-85 are rejected under 35 U.S.C. § 103(a) as being

unpatentable Santeler et al. (US Patent 6,223,301 hereafter

referred to as Santeler) in view of Arnold et al. (US Patent

6,279,128 hereafter referred to as Arnold).

As per claim 1:

Santeler substantially teaches the invention. Santeler

teaches:

- a system for detecting errors in a memory device [abstract,

fig. 3, col. 2, lines 13-27]

comprising:

- a memory sub-system [fig. 3, col. 2, lines 13-15];

- a plurality of memory cartridges configured to stored data

words (i.e., memory blocks, memory banks, memory modules) [col.

4, lines 35-42];

- a cleansing device configured to periodically initiate an

internal READ command to plurality of memory cartridges in

response to an event, the internal READ command being issued to

plurality of memory cartridges on a memory network bus [col. 5,

lines 9-18 and col. 6, lines 10-34];

- host controller (i.e., controller) coupled to the memory and

comprising error detection logic configured to detect errors

[col. 5, lines 20-37] from memory (i.e., memory blocks, memory

banks, memory modules) [col. 4, lines 35-42].

Santeler does not explicitly teach:

- a monitoring device configured to monitoring the memory

network bus and configured to change the frequency of periodic

initiations of the internal READ command.

However, Santeler does disclose capability of:

- a computer system having a fault tolerant RAID array

[abstract, fig. 3, col. 2, lines 13-27]

 comprising:

- a data transmission connectivity among plurality of memory

modules, a IDE control, a central control logic, a memory

controller, etc... via network bus [fig. 3, col. 3, lines 39

through col. 4, lines 42];

- memory module control logic, memory address control logic,

memory controller, a central control logic used to calculate

parity data as well as to initiate READ commands for configuring

networking bus [fig. 3, col. 5, lines 13-24 and col. 5, lines

20-37];

- a data/error code correction (ECC) used error detection and

correction [col. 4, lines 59-65 and col. 5, lines 25-38].

In addition, Arnold explicitly teaches:

- a system for continuous monitoring and detection of memory system [abstract, fig. 1, col. 9, lines 36-42];

comprising:

- plurality of DRAM memory array (i.e., memory modules) with controller connected to ECC, scrub sequencer, address controller, etc... [fig. 2, col. 5, lines 12-26];

- a monitoring capability to performing and configuring READ commands based on network bus request, memory process, as well as scrub sequencer [col. 6, lines 6-53].

Therefore, it would have been obvious to a person having ordinary skill in the art at the time the invention was made first, to realize the Santeler's computer system having a fault tolerant RAID comprising a data transmission connectivity among plurality of memory modules, a IDE control, a central control logic, a memory controller, etc... via network bus and more specifically the memory module control logic, memory address control logic, memory controller, a central control logic used to calculate parity data as well as to initiate READ commands for configuring networking bus as being the

monitoring device configured to monitoring the memory network

bus and configured to change the frequency of periodic

initiations of the internal READ command as claimed by

Applicant. This is because the Santeler's computer system having

a fault tolerant RAID does clearly perform the data error

detection and correction via a control logics that establishes

and initiates the operational commands such as READ, WRITE

requests, etc.... in supporting the memory error detection and

correction. It is further obvious to an ordinary skill in the

art to understand the Santeler's control logic does perform the

programming or configuring (i.e., monitoring) its capability to

add, distribute, and calculate the parity data in the memory

modules; second, one would modify the Santeler's computer system

having a fault tolerant RAID array to explicitly including the a

monitoring capability to performing and configuring READ

commands based on network bus request, memory process, as well

as scrub sequencer as taught by Arnold's system for continuous

monitoring and detection of memory system in supporting data

transmission/processing within memory data modules via control

logic capability.

This modification would have been obvious because a person

having ordinary skill in the art would have been motivated to do

so to provide the memory system with plurality of memory modules

or memory arrays and more specifically to a RAID array memory

with a mechanism to enhance data performance/monitoring, data

availability/reliability, and data configuring/exchanging

operation via EEC means for data recovery process. It is further

obvious because by utilizing this approach, memory system with a

processor-based computer can be realized in high performance

throughput with a high reliability and flexibility memory

environment. That will correctly provide optimum data

availability and transmission throughput among end users real-

time communication and execution.

As per claims 2-6:

Santeler substantially teaches the invention. Santeler

teaches:

- a system for detecting errors in a memory device [abstract,

fig. 3, col. 2, lines 13-27]

comprising:

- a plurality of memory cartridges configured to stored data

words (i.e., memory blocks, memory banks, memory modules) [col.

4, lines 35-42];

- plurality of memory modules comprising a Dual Inline Memory

Module (DIMM) [col. 3, lines 45-55];

- memory and comprising error detection logic configured to

detect errors [col. 5, lines 20-37] from memory (i.e., memory

blocks, memory banks, memory modules) [col. 4, lines 35-42].

- memory sub-system comprising five memory modules [col. 2,

lines 59-61, col. 4, lines 1-7, and col. 4, lines 35-42].

Santeler does not explicitly teach:

- Synchronous Dynamic Random Access Memory (SDRAM) device.

However, Santeler does disclose capability of:

- a computer system having a fault tolerant RAID array

[abstract, fig. 3, col. 2, lines 13-27]

 comprising:

- a RAID array, SIMM, DIMM memory devices [col. 4, lines 35-42

and col. 7, lines 49-59];

In addition, Arnold explicitly teaches:

- a system for continuous monitoring and detection of memory

system [abstract, fig. 1, col. 9, lines 36-42];

comprising:

- plurality of DRAM memory array (i.e., memory modules) with

controller connected to ECC, scrub sequencer, address

controller, etc...   [fig. 2, col. 5, lines 12-26];

Therefore, it would have been obvious to a person having ordinary skill in the art at the time the invention was made to realize the Santeler's computer system having a fault tolerant RAID comprising a data transmission connectivity among plurality of memory modules including a RAID array, SIMM, DIMM memory devices and the Arnold's system for continuous monitoring and detection of memory system including

plurality of DRAM memory array do embedded the Synchronous Dynamic Random Access Memory (SDRAM) device as indicated by Applicant. This is because the SDRAM memory device is part of RAID, SIMM, and DIMM families of memory. Therefore, it would have been obvious to an ordinary skill in the art to readily use and apply the SDRAM memory device within the error detection and correction environment.

As per claims 7-12:

Santeler substantially teaches the invention. Santeler teaches:

- a system for detecting errors in a memory device [abstract, fig. 3, col. 2, lines 13-27]

comprising:

- a memory sub-system [fig. 3, col. 2, lines 13-15];

- a plurality of memory cartridges configured to stored data

words (i.e., memory blocks, memory banks, memory modules) [col.

4, lines 35-42];

- a cleansing device configured to periodically initiate an

internal READ command to plurality of memory cartridges in

response to an event, the internal READ command being issued to

plurality of memory cartridges on a memory network bus [col. 5,

lines 9-18 and col. 6, lines 10-34];

- memory module control logic, memory address control logic,

memory controller, a central control logic used to calculate

parity data as well as to initiate READ commands for configuring

networking bus [fig. 3, col. 5, lines 13-24 and col. 5, lines

20-37];

- a data/error code correction (ECC) used error detection and

correction [col. 4, lines 59-65 and col. 5, lines 25-38].

- the event comprising an operator instruction (i.e., correction

code) and the expiration of a timer [col. 2, lines 21-27 and

col. 2, lines 47-54].

    In addition, Arnold explicitly teaches:

- a system for continuous monitoring and detection of memory

system [abstract, fig. 1, col. 9, lines 36-42];

comprising:

- a monitoring capability to performing and configuring READ

commands based on network bus request, memory process, as well

as scrub sequencer [col. 6, lines 6-53].

- the event comprising an operator instruction (i.e., code

signature) [abstract, col. 4, lines 10-21].

As per claims 13-20:

Santeler substantially teaches the invention. Santeler

teaches:

- a system for detecting errors in a memory device [abstract,

fig. 3, col. 2, lines 13-27]

comprising:

- a memory sub-system [fig. 3, col. 2, lines 13-15];

- a plurality of memory cartridges configured to stored data

words (i.e., memory blocks, memory banks, memory modules) [col.

4, lines 35-42];

- a cleansing device configured to periodically initiate an

internal READ command to plurality of memory cartridges in

response to an event, the internal READ command being issued to

plurality of memory cartridges on a memory network bus [col. 5,

lines 9-18 and col. 6, lines 10-34];

- host controller (i.e., controller) coupled to the memory and

comprising error detection logic configured to detect errors

[col. 5, lines 20-37] from memory (i.e., memory blocks, memory

banks, memory modules) [col. 4, lines 35-42].

Santeler does not explicitly teach:

- a monitoring device coupled to the arbiter and the number of

request to the arbiter are changed in response to requested

counted by plurality of counters.

However, Santeler does disclose capability of:

- a computer system having a fault tolerant RAID array

[abstract, fig. 3, col. 2, lines 13-27]

 comprising:

- a data transmission connectivity among plurality of memory

modules, a IDE control, a central control logic, a memory

controller, etc... via network bus [fig. 3, col. 3, lines 39

through col. 4, lines 42];

- memory module control logic, memory address control logic,

memory controller, a central control logic used to calculate

parity data as well as to initiate READ commands requests for

configuring networking bus [fig. 3, col. 5, lines 13-24 and col.

5, lines 20-37];

- mapping of memory and access the memory via control signals
(i.e., memory access scheduling and control) [col. 6, lines 63
through col. 7, lines 10];

- a data/error code correction (ECC) used for error detection
and correction and parity bit calculation (i.e., counters used
therein) [col. 4, lines 59-65 and col. 5, lines 25-38].

    In addition, Arnold explicitly teaches:

- a system for continuous monitoring and detection of memory
system [abstract, fig. 1, col. 9, lines 36-42];

comprising:

- plurality of DRAM memory array (i.e., memory modules) with
controller connected to ECC, scrub sequencer, address
controller, etc... [fig. 2, col. 5, lines 12-26];

- a monitoring capability to performing and configuring READ
commands based on network bus request, memory process, as well
as scrub sequencer [col. 6, lines 6-53].

Therefore, it would have been obvious to a person having
ordinary skill in the art at the time the invention was made
first, to realize the Santeler's computer system having a fault
tolerant RAID comprising a central control logic used to
calculate parity data as well as to initiate READ commands

requests for configuring networking bus, mapping of memory and
access the memory via control signals (i.e., memory access
scheduling and control), and a data/error code correction (ECC)
used for error detection and correction and parity bit
calculation (i.e., counters used therein)
as being the a monitoring device coupled to the arbiter and the
number of request to the arbiter are changed in response to
requested counted by plurality of counters as claimed by
Applicant. This is because the Santeler's computer system having
a fault tolerant RAID does clearly perform the data error
detection and correction via a control logics as well as
scheduling and access control in supporting the memory fault
tolerant system.; second, one would modify the Santeler's
computer system having a fault tolerant RAID array to explicitly
including the a monitoring capability to performing and
configuring READ commands based on network bus request, memory
process, as well as scrub sequencer as taught by Arnold's system
for continuous monitoring and detection of memory system in
supporting data transmission/processing within memory data
modules via control logic capability.
This modification would have been obvious because a person
having ordinary skill in the art would have been motivated to do
so to provide the memory system with plurality of memory modules

or memory arrays and more specifically to a RAID array memory

with a mechanism to enhance data performance/monitoring, data

availability/reliability, and data configuring/exchanging

operation via EEC means for data recovery process.

As per claims 21-38, 43:

Due to the similarity of claims 21-38 to claims 1-20 except

for a memory sub-system comprising capabilities of plurality of

memory cartridge, a cleansing device, a monitoring device,

etc... instead of a system for detecting errors in a memory

device including a memory sub-system comprising capabilities of

plurality of memory cartridge, a cleansing device, a monitoring

device, etc...Therefore, theses claims are also rejected under

the same rationale applied against claims 1-20. In addition, all

of the limitations have been noted in the rejection as per

claims 1-20.

As per claims 39-42, 44-66:

These claims are similar to claims 1-20. The only minor

different is these claims introduce:

- a memory engine configured to correct the error detected in

data word;

- scrubbing control logic configured to request a write-

back to memory;

- a content addressable memory (CAM).

However, Santeler teaches:

Santeler substantially teaches the invention. Santeler

teaches:

- a system for detecting errors in a memory device [abstract,

fig. 3, col. 2, lines 13-27]

comprising:

- a memory sub-system [fig. 3, col. 2, lines 13-15];

- a plurality of memory cartridges configured to stored data

words (i.e., memory blocks, memory banks, memory modules) [col.

4, lines 35-42];

- a cleansing device configured to periodically initiate an

internal READ/WRITE command to plurality of memory cartridges in

response to an event, the internal READ/WRITE command being

issued to plurality of memory cartridges on a memory network bus

[col. 5, lines 9-18 and col. 6, lines 10-34];

- memory module control logic, memory address control logic

(i.e., CAM), memory controller, a central control logic used to

calculate parity data as well as to initiate READ commands for

configuring networking bus [fig. 3, col. 5, lines 13-24 and col.

5, lines 20-37];

- a data/error code correction (ECC) used error detection and

correction [col. 4, lines 59-65 and col. 5, lines 25-38].

    In addition, Arnold explicitly teaches:

- a system for continuous monitoring and detection of memory

system [abstract, fig. 1, col. 9, lines 36-42];

comprising:

- plurality memory array with controller connected to ECC, scrub

sequencer, address controller, etc... [fig. 2, col. 5, lines

12-26];

- a scrubbing means used to read/write data [col. 9, lines 35-

48];

- a monitoring capability to performing and configuring READ

commands based on network bus request, memory process, as well

as scrub sequencer [col. 6, lines 6-53].

Therefore, these claims are also rejected under the same

rationale applied against claims 1-20. In addition, all of the

limitations have been noted in the rejection as per claims 1-20.

As per claims 67-85:

    Firstly, due to the similarity of claims 67-85 to claims 1-

20 except for a method for dynamically scheduling access to a

memory steps including monitoring activity on a memory step,

periodically initiating internal READ commands step, etc...

instead of instead of a system for detecting errors in a memory

device including a memory sub-system comprising capabilities of

plurality of memory cartridge, a cleansing device configured to

periodically initiating internal READ commands, a monitoring

device, etc...Therefore, theses claims are also rejected under

the same rationale applied against claims 1-20. In addition, all

of the limitations have been noted in the rejection as per

claims 1-20.

Secondly, a compared a threshold, RAID memory are also

introduced in dependent claims 72,73, 84, and 85.

However, Santeler teaches:

Santeler teaches:

- a computer system having a fault tolerant RAID array

[abstract, fig. 3, col. 2, lines 13-40]

comprising:

- a memory sub-system [fig. 3, col. 2, lines 13-15];

- a plurality of memory cartridges configured to stored data

words (i.e., memory blocks, memory banks, memory modules) [col.

4, lines 35-42];

- a data/error code correction (ECC) used error detection and

correction [col. 4, lines 59-65 and col. 5, lines 25-38].

In addition, Arnold explicitly teaches:

- a system for continuous monitoring and detection of memory

system [abstract, fig. 1, col. 9, lines 36-42];

comprising:

- plurality memory array with controller connected to ECC, scrub

sequencer, address controller, etc... [fig. 2, col. 5, lines

12-26];

- a scrubbing means used to read/write data [col. 9, lines 35-

48];

- a monitoring capability to performing and configuring READ

commands based on network bus request, memory process, as well

as scrub sequencer [col. 6, lines 6-53].

- a compared a threshold in supporting the error detection and

correction system [col. 7, lines 23-43]

Therefore, these claims are also rejected under the same

rationale applied against claims 1-20. In addition, all of the

limitations have been noted in the rejection as per claims 1-20.

Conclusion

6.   The prior art made of record and not relied upon is

considered pertinent to applicant's disclosure.

7.   A shortened statutory period for response to this action is
set to expired THREE (3) months, ZERO days from the date of this
letter.   Failure to respond within the period for response will
cause the application to be abandoned. 35 U.S.C. 133.

1.   Any inquiry concerning this communication or earlier
communications from the examiner should be directed to Dieu-Minh
Le whose telephone number is (703) 305-9408.   The examiner can
normally be reached on Monday-Thursday from 6:30 AM to 4:00 PM.
The examiner can also be reached on alternate Fridays.
        If attempts to reach the examiner by telephone are
unsuccessful, the examiner's supervisor, Robert Beausoliel, can
be reached on (703)305-9713.   The fax phone number for this
Group is (703)746-7240.

Any inquiry of a general nature or relating to the status
of this application should be directed to the Group receptionist
whose telephone number is (703) 305-3900.
        Any response to this action should be mailed to:
                Commissioner of Patents and Trademarks
                Washington, D.C. 20231
        or faxed to:
                (703) 746-7239, (for formal communications
                intended for entry)
        Or:
                (703) 746-7240 (for informal or draft
                communications, please label "PROPOSED" or
                "DRAFT")

Hand-delivered responses should be brought to Crystal

Park II, 2121 Crystal Drive, Arlington. VA., Sixth

Floor   (Receptionist).

**DIEU-MINH THAI LE
PRIMARY EXAMINER
ART UNIT 2184**

DML
9/25/03